

AMENDMENTS TO THE SPECIFICATION:

Please replace the paragraph numbered 0039 in the body of the specification with the following paragraph:

[0039] The cartridge has a circular storage medium 27 (shown in part in FIG. 9) with a center 36, a periphery 37, and a data storage surface 38. The medium 27 may have a storage surface on both sides 38. The storage medium 27 is protected within the housing 10. Referring in particular to FIG. 10, the housing 10 is structured to provide an access path through access opening 25 to allow the head 42 of the acutator 31 to be moved back and forth into proximity with the data storage surface 38 of the medium. The storage medium 27 is rotated by a drive rotator or motor 18 around the center 36 when the removable cartridge is mounted in the drive.

VERSION OF AMENDMENTS TO THE SPECIFICATION SHOWING CHANGES:

[0039] The cartridge has a circular storage medium 27 (shown in part in FIG. 9 ~~and FIG. 10~~) with a center 36, a periphery 37, and a data storage surface 38. The medium 27 may have a storage surface on both sides 38. The storage medium 27 is protected within the housing 10. ~~Referring in particular to FIG. 10, t~~The housing 10 is structured to provide an access path through access opening 25 to allow the head 42 of the acutator 31 to be moved back and forth into proximity with the data storage surface 38 of the medium. The storage medium 27 is rotated by a drive rotator or motor 18 around the center 36 when the removable cartridge is mounted in the drive.